

**WL1S2****SS 304****Sems Screws(Hex Screw with Assembled Plain Washer & Spring Washer)**

Size→ Parameter↓	M3x0.5	M4x0.7	M5x0.8	M6x1.0	M8x1.25	M10x1.5
dk (max)	7.00	9.00	10.00	12.00	16.00	17.00
dk (min)	6.60	8.60	9.60	11.50	15.50	16.50
k (max)	2.30	3.10	3.80	4.30	5.60	6.60
k (min)	1.70	2.50	3.20	3.70	5.00	6.15
s (max)	5.50	7.00	8.00	10.00	13.00	17.00
s (min)	0.45	0.70	0.90	1.50	0.90	1.50

Quote the item code given below with your order/enquiries.

Dimensions in mm

Size→ Length↓	M3x0.5	M4x0.7	M5x0.8	M6x1.0	M8x1.25	M10x1.5
5	WL1S203005					
6	WL1S203006	WL1S204006				
8	WL1S203008	WL1S204008	WL1S205008			
10	WL1S203010	WL1S204010	WL1S205010	WL1S206010		
12	WL1S203012	WL1S204012	WL1S205012	WL1S206012		
14	WL1S203014	WL1S204014	WL1S205014	WL1S206014		
16	WL1S203016	WL1S204016	WL1S205016	WL1S206016	WL1S205016	
18	WL1S203018	WL1S204018	WL1S205018	WL1S206018	WL1S205018	
20	WL1S203020	WL1S204020	WL1S205020	WL1S206020	WL1S205020	WL1S206020
25	WL1S203025	WL1S204025	WL1S205025	WL1S206025	WL1S205025	WL1S206025
30	WL1S203030	WL1S204030	WL1S205030	WL1S206030	WL1S205030	WL1S206030
35		WL1S204035	WL1S205035	WL1S206035	WL1S205035	WL1S206035
40		WL1S204040	WL1S205040	WL1S206040	WL1S205040	WL1S206040
45		WL1S204045	WL1S205045	WL1S206045	WL1S205045	WL1S206045
50		WL1S204050	WL1S205050	WL1S206050	WL1S205050	WL1S206050

Sizes in BLUE are non-preferred. Availability is limited and MOQ is higher.

Data is strictly informative

Note: All Austenitic Stainless Steel Fasteners may exhibit some magnetic properties due to the manufacturing process.**Refer:** ISO 3506-2 Annex F