


W6vNS2

SS - 304



Hex Nut ASME B 18.2.2 (UNF Series)

Quote the item code given below with your order/enquiries.

Dimensions in inches

Nominal Size(d)	Item Code	Width Across Corners e	Width Across flat S			Thickness m	
Thread Size		e min	Nom	Min	Max	Min	Max
2-64	W6vNS226400	0.205	3/16"	0.180	0.188	0.057	0.066
4-48	W6vNS244800	0.275	1/4"	0.241	0.25	0.087	0.098
6-40	W6vNS264000	0.344	5/16"	0.302	0.312	0.102	0.114
8-36	W6vNS283600	0.378	11/32"	0.332	0.344	0.117	0.130
10-32	W6vNS213200	0.413	3/8"	0.362	0.375	0.117	0.130
12-28	W6vNS212280	0.482	7/16"	0.423	0.438	0.148	0.161
1/4-28	W6vNS262000	0.488	7/16"	0.428	0.438	0.178	0.193
5/16-24	W6vNS279000	0.557	1/2"	0.489	0.500	0.208	0.225
3/8-24	W6vNS291000	0.628	9/16"	0.551	0.563	0.239	0.257
7/16-20	W6vNS211000	0.768	11/16"	0.675	0.688	3/8"	3/8"
1/2-20	W6vNS213000	0.840	3/4"	0.736	0.750	7/16"	7/16"
9/16-18	W6vNS214000	1.010	7/8"	0.861	0.875	31/64"	31/64"
5/8-18	W6vNS215000	1.051	15/16"	0.922	0.938	36/64"	36/64"
3/4-16	W6vNS219000	1.240	1 1/8"	1.088	1.125	41/64"	41/64"
7/8-14	W6vNS223000	1.447	1 5/16"	1.269	1.312	3/4"	3/4"
1-14	W6vNS225000	1.653	1 1/2"	1.450	1.500	55/64"	55/64"
1 1/8-12	W6vNS228000	1.859	1 11/16"	1.631	1.688	31/32"	31/32"
1 1/4-12	W6vNS231000	2.066	1 7/8"	1.812	1.875	1 1/16"	1 1/16"
1 1/2-12	W6vNS238000	2.480	2 1/4"	2.175	2.250	1 9/32"	1 9/32"

Sizes in BROWN are non-preferred. Availability is limited and MOQ is higher.

Data is strictly informative

Note: All Austenitic Stainless Steel Fasteners may exhibit some magnetic properties due to the manufacturing process.

Refer: ISO 3506-2 Annex F