



WPWSS2

AISI 304

Sems Screws(Pan Screw with Assembled Small OD Plain Washer & Spring Washer)

Size→ Parameter↓	(M2x0.4)	M2.5x0.45	M3x0.5	M4x0.7	(M5x0.8)	(M6x1.0)
dk (max)	3.50	4.50	5.50	7.00	9.00	10.50
dk (min)	3.20	4.20	5.20	6.64	8.50	9.80
k (max)	1.50	1.90	2.30	2.90	3.50	4.30
k (min)	1.26	1.66	2.01	2.61	3.20	4.00
D max)	4.50	5.00	6.00	8.00	9.00	11.00
a (max)	2.50	3.00	3.30	4.00	4.50	6.00
x (max)	0.80	0.90	1.00	1.40	1.60	1.80
h (nom)	1.00	1.20	1.60	1.80	2.40	3.20
m (ref)	1.90	2.70	3.50	4.40	4.90	5.50
s (max)	0.30	0.55	0.55	0.90	1.10	1.70
s (min)	0.30	0.45	0.45	0.70	0.90	1.50

Quote the item code given below with your order/enquiries.

Dimensions in mm

Size→ Length↓	(M2x0.4)	M2.5x0.45	M3x0.5	M4x0.7	(M5x0.8)	(M6x1.0)
5	WPWSS202105	WPWSS225105	WPWSS203105			
6	WPWSS202106	WPWSS225106	WPWSS203106	WPWSS204106		
8	WPWSS202108	WPWSS225108	WPWSS203108	WPWSS204108	WPWSS205108	
10	WPWSS202110	WPWSS225110	WPWSS203110	WPWSS204110	WPWSS205110	WPWSS206110
12	WPWSS202112	WPWSS225112	WPWSS203112	WPWSS204112	WPWSS205112	WPWSS206112
14	WPWSS202114	WPWSS225114	WPWSS203114	WPWSS204114	WPWSS205114	WPWSS206114
16	WPWSS202116	WPWSS225116	WPWSS203116	WPWSS204116	WPWSS205116	WPWSS206116
20		WPWSS225120	WPWSS203120	WPWSS204120	WPWSS205120	WPWSS206120
25		WPWSS225125	WPWSS203125	WPWSS204125	WPWSS205125	WPWSS206125
30			WPWSS203130	WPWSS204130	WPWSS205130	WPWSS206130
35				WPWSS204135	WPWSS205135	WPWSS206135
40					WPWSS205140	WPWSS206140
45						WPWSS206145
50						WPWSS206150

Sizes in BLUE are non-preferred. Availability is limited and MOQ is higher.

Data is strictly informative

Note: All Austenitic Stainless Steel Fasteners may exhibit some magnetic properties due to the manufacturing process.

Refer: ISO 3506-2 Annex F