





WITRUS PRIVATE LIMITED

#06 Andrahalli Main Road Peenya 2nd Stage Vishwaneedam Post
Bangalore - 560091

W2NSS

SS Hardened



SELF CLINCH NUT SP (For SS Sheet Hardness Upto HRB 90)

Size→ Dimension↓	Tol	M2x0.4	M2.5x0.45	M3x0.5	M3.5x0.6	M4x0.7	M5x0.8	M6x1.0	M8x1.25	M10x1.5
Collar dia d2	max	4.22	4.22	4.22	4.73	5.38	6.38	8.72	10.47	13.97
Nut dia d3	±0.25	6.25	6.35	6.35	7.10	7.87	8.64	11.18	12.70	17.35
Nut thickness m	±0.25	1.50	1.50	1.50	1.50	2.00	2.00	4.08	5.47	7.48
Hole Size in Sheet	+0.08	4.25	4.25	4.25	4.75	5.40	6.40	8.75	10.50	14.00
Minimum edge distance to hole centre		4.80	4.80	4.80	5.60	6.90	7.10	8.60	9.70	13.50

Quote the item code given below with your order/ inquiries:

Dimensions in mm

Size	Shank Code	Item Code	Min Sheet Thickness sm	h (Shank) Max	Press In KN		Push out N		Torque out Nm	
					Aluminium	Steel	Aluminium	Steel	Aluminium	Steel
M2x0.4	0	W2NSS02000	0.80	0.77	6.7 - 8.9	11.2 - 15.6	280	470	0.90	1.47
	1	W2NSS02001	1.00	0.97			400	550	1.13	1.70
	2	W2NSS02002	1.40	1.38			750	1010	1.47	2.03
M2.5x0.45	0	W2NSS20500	0.80	0.77	6.7 - 8.9	11.2 - 15.6	280	470	0.90	1.47
	1	W2NSS20501	1.00	0.97			400	550	1.13	1.70
	2	W2NSS20502	1.40	1.38			750	1010	1.47	2.03
M3x0.5	0	W2NSS03000	0.80	0.77	6.7 - 8.9	11.2 - 15.6	280	470	0.90	1.47
	1	W2NSS03001	1.00	0.97			400	550	1.13	1.70
	2	W2NSS03002	1.40	1.38			750	1010	1.47	2.03
M3.5x0.6	0	W2NSS30500	0.80	0.77	11.2 - 13.4	13 - 26	280	490	1.80	2.30
	1	W2NSS30501	1.00	0.97			400	570	2.30	2.71
	2	W2NSS30502	1.40	1.38			800	1080	2.60	3.20
M4x0.7	0	W2NSS04000	0.80	0.77	11.2 - 13.4	18 - 27	300	490	2.37	2.95
	1	W2NSS04001	1.00	0.97			470	645	2.60	4.00
	2	W2NSS04002	1.40	1.38			970	1250	4.00	5.10
M5x0.8	0	W2NSS05000	0.80	0.77	11.2 - 15.6	18 - 38	300	530	3.00	3.60
	1	W2NSS05001	1.00	0.97			480	800	3.60	4.50
	2	W2NSS05002	1.40	1.38			845	1112	5.70	6.80
M6x1.0	0	W2NSS06000	1.20	1.15	11.2 - 13.4	27 - 36	970	1380	7.90	13.00
	1	W2NSS06001	1.40	1.38			1540	1760	10.20	17.00
	2	W2NSS06002	2.30	2.21			1680	1850	14.10	19.20
M8x1.25	1	W2NSS08001	1.40	1.38	11.2 - 15.6	27 - 36	1570	1870	13.60	18.70
	2	W2NSS08002	2.30	2.21			1720	1980	18.10	20.30
M10x1.5	1	W2NSS08001	2.31	2.21	18 - 32	32 - 50	1760	2020	32.70	36.20
	2	W2NSS08002	3.18	3.05			1880	2150	36.20	39.60

Sizes in BLUE are non-preferred. Availability is limited and MOQ is higher.

Data is strictly informative

Note: All Austenitic Stainless Steel Fasteners may exhibit some magnetic properties due to the manufacturing process.

Refer: ISO 3506-2 Annex F