



WP5TBS4

SS 316

5 Lobe Pin Button Head Self Tapping Screw
(Multi Security Screw)

Dia d	3.5	4.2	4.8	5.5
ISO Size	#6	#8	#10	#12
dK min	6.50	7.20	9.10	10.00
dK max	6.90	7.60	9.60	10.40
k min	2.35	2.00	2.40	2.85
k max	2.65	2.30	2.80	3.25
Tool Size	F10	F15	F25	F27

Quote the item code given below with your order/ inquiries:

Dimensions in mm

Dia d	3.5	4.2	4.8	5.5
ISO Size	#6	#8	#10	#12
13 [1/2"]	WP5TBS406013			
19 [3/4"]	WP5TBS406019	WP5TBS408019	WP5TBS410019	
25 [1"]	WP5TBS406025	WP5TBS408025	WP5TBS410025	WP5TBS412025
32 [1-1/4"]		WP5TBS408032	WP5TBS410032	
38 [1-1/2"]		WP5TBS408038	WP5TBS410038	WP5TBS412038
50 [2"]		WP5TBS408050	WP5TBS410050	WP5TBS412050
63 [2-1/2"]				WP5TBS412063
75 [3"]				WP5TBS412075

Sizes in BROWN are non-preferred. Availability is limited and MOQ is higher.

Data is strictly informative.

5-LOBE PIN SECURITY BIT

Bit Size	Part Number
F10	WPBC610000
F15	WPBC615000
F20	WPBC620000
F25	WPBC625000
F27	WPBC627000



Catalogue Data Sheet **WPBC6**

Note: All Austenitic Stainless Steel Fasteners may exhibit some magnetic properties due to the manufacturing process.

Refer: ISO 3506-2 Annex F

